


SPECIFICATIONS

Weight – approx. 1.8 kg



Terminal Module Thermal Printer TM-T88IV

PRINT METHOD	Thermal Line Printing		
PRINT FONT	FONT	9 x 17 / 12 x 24	
	COLUMN CAPACITY (COLUMNS)	56 / 42	
	CHARACTER SIZE (MM)	0.99 (W) x 2.4 (H) / 1.41 (W) x 3.39 (H)	
	CHARACTER SET	95 Alphanumeric, 37 International, 128 x 11 Graphic, Traditional / Simple Chinese, Japanese, Korean, Thai	
		BARCODE	UPC-A/E, CODE 39 / 93 / 128, EAN 8 / 13, ITF, CODABAR
		TWO-DIMENSIONAL CODE	PDF 417, QRCode
	CHARACTER PER INCH	20.0 cpi / 15.0 cpi	
INTERFACE	STANDARD	RS-232, Bi-Directional Parallel	
	DEALER OPTION	RS-485; USB; 10/100 Base T Ethernet I/F	
DATA BUFFER	4KB or 45 Bytes		
PRINTER SPEED	7.9"/ Sec (200mm) Graphics and Text 3.9"/ Sec in 2 Colour Print Mode		
PAPER	DIMENSIONS (MM)	ROLL PAPER	79.5 ± 0.5 (W) x Diameter 83.0
	THICKNESS (MM)		0.06 to 0.07
POWER	24 VDC ± 7%		
POWER CONSUMPTION	Approx. 1.8 A (Mean)		
D.K.D. FUNCTION	2 Drivers		
RELIABILITY	MTBF	360,000 Hours	
	MCBF	52,000,000 Lines	
	AUTO CUTTER	1.5 Million Cuts	
DIMENSIONS (D X W X H)	195 x 145 x 148 mm		
WEIGHT	Approx. 1.8 kg		
CASE COLOUR	(ECW) Epson Cool White (EDG) Epson Dark Grey		
POWER SUPPLY	PS-180		
OPTION	Wall-Hanging Bracket WH-10		
SAFETY STANDARDS	UL1950 / CSA / C22.2 No. 950		



ESC/POS®

Epson is the registered trademark of SEIKO EPSON CORPORATION.

All other product names and other company names used herein are for identification purpose only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Scan/Print samples shown herein are simulations. Specifications are subject to change without notice.

EPSON
EXCEED YOUR VISION

INDIA — (91) 80-305-15000, CALCUTTA – 228 31589/90,
CHENNAI — 302 77500, MUMBAI – 282 61515/16/17, NEW DELHI – 306 15000
INDONESIA — (62) 21-572-3161
MALAYSIA — (60) 3-562-88288
PHILIPPINES — (632) 813-6567
SINGAPORE — (65) 6586-5500, (65) 6586-3111
THAILAND / INDOCHINA — (662) 685-9888

Dealer's Stamp

www.epson.com.sg

Printed October 2006