




Dimensions(mm)


Specifications

Nominal Voltage	12V	
Rated Capacity(20 hour rate)	26AH	
Dimensions ±1mm	Length	166mm(6.54")
	Width	175mm(6.89")
	Height	125mm(4.92")
	Total Height (with terminals)	
Weight	Approx.9.75kg (21.45lbs)	
Standard Terminal	L1	

Discharge Characteristics(20°C ,68°F)


Electrical Specifications

Capacity 77°F (25°C)	20 hour rate (1.3A)	26AH
	10 hour rate (2.42A)	24.2AH
	5 hour rate (4.42A)	22.1AH
	1 hour rate (15.6A)	15.6AH
Internal Resistance	Fully charged battery 77°F (25°C)	13m Ω
Capacity Affected by Temperature (20 hour rate)	104°F (40°C)	102%
	77°F (25°C)	100%
	32°F (0°C)	85%
	5°F (-15°C)	65%
Self-Discharge 77°F (25°C)	Capacity after 3 month storage	92%
	Capacity after 6 month storage	83%
	Capacity after 12 month storage	65%
Charge Constant Voltage	Cycle:Initial Charging Current less than7.80A Voltage14.4-15.0V 77°F (25°C) Standby:Voltage13.5-13.8V 77°F (25°C)	

Discharge Characteristics(0°C/32°F ,40°C /104°F)
